ma isafe











CleanAIR® Low Weight CleanAIR®

RFU837

The highest level of breathing protection with enhanced inner airflow regulation and a visor with excellent optical and mechanical features make this universal light face shield a true leader of its class.

Features and Benefits

- The highest class of breathing protection TH3
- · Enhanced inner airflow regulation
- Light weight only 380g
- Excellent optical quality EN 166 class 1
- · High mechanical resistance of the visor
- · Antifog / antiscratch coating
- Safety helmet compatible
- Neoprene or textile face seal option
- · Easy to use and adjust
- Fast and simple maintenance

Applications

- Building Industry
- Automotive industry Shipbuilding
- Heavy Industry
- Refineries



Product Code	Description	Pack Qty	Boxes per Carton
RFU837	UniMask Protective Face Shield	1	5
RPA530	CleanAIR AerGo PAPR Belt Unit	1	5
RCA544	CleanAIR Basic EVO PAPR Belt Unit	1	5
RCF549	CleanAIR Flow Master with belt and flow indicator	1	5
RFH529	Light Flexi Hose	1	5
RUV842	Spare Protective Visor for UniMask - Clear	1	5
RUV843	Spare Protective Visor for UniMask - Amber	1	5
RUV844	Spare Protective Visor for UniMask - Shade 3	1	5
RUV845	Spare Protective Visor for UniMask - Shade 5	1	5





UniMask Protective Face Shield Features

Easy and Quick Changing of the Visor

In case the visor has to be replaced or separately cleaned, it can be easily removed and attached back to the hood using two simple locking knobs.



Inner Airflow Regulation





Quickly Exchangeable Face Seal with Easy Maintenance

The face seal ensures secure and comfortable fit for the wearer. Thanks to a fast clickin system the face seal can be easily and quickly removed and attached back.

The face seals can be washed in a washing





Safety Helmet Compatible

The UniMASK can be used with a wide range of standard safety helmets to provide a handy solution of head protection combined with protection of the face and respiratory!



reddot winner 2020 best of the best

CLICK HERE FOR PRODUCT SPEC

there's safe and there's Maxisafe.

Your Maxisafe Dealer:

ma isafe

CleanAIR® Chemical 2F PAPR System





Features & Benefits

- · Compact design and low weight
- Compatible with a hood, mask or ventilated protective suit
- High mechanical and chemical resistance
- High durability 1.5m drop test
- Increased ingress protection allows decontamination by shower or even full immersion (IP64/IP65/IP68)
- Full colour display clearly shows all the relevant information - filter clogging, battery charge, airflow
- Flow Control system maintains constant airflow regardless of the level offilter clogging or battery charge
- Short battery recharging time < 3 hours
- Audiovisual alarm
- Multilingual user interface
- Wide selection of filters available with a standard DIN connection thread (40x1/7)

Applications

- · Heavy industrial environments including chemical and pharmaceutical industry
- Remediation operations, laboratories
- First responders and emergency teams
- Biological protection

Product Details

Product Code: R510000FDA-AUS Weight: 960 g (including

standard battery)

Dimensions: 240 mm x 110 mm x 120 mm Adjustable 160 -235 lpm

Airflow: Alarm: Audio, visual Operation* <10 / < 3 h

/ charging

time:

Li-lon 14.4 V / 2.6 Ah **Battery:**

(standard)

Standards

EN 12941 TH3 EN 12942 TM3 Ingress protection - IP64/IP65/IP68 IIIC 135°C Dc

Available Head Top Combinations



UniMask



Grinding R710300







Full Face





Full Colour Display

Full colour display cleary shows all the relevant information – airflow, battery charge, filter clogging.

Filter Timer

Just set the filter timer according to your needs and the system will trigger the alarm when the filter replacement is required.



Compact Design and Low Weight

The thought-out design with smooth surface allows easy decontamination by shower or even full immersion.



Heavy Duty Battery

The high capacity battery doubles the operation time. No more necessary changing or charging the battery during a long shift even when using gas and combined filters.

Battery Li-lon Heavy Duty, Li-lon 14,4V / 5,2Ah R510020

Automatic Closing System

The unique automatic closing system prevents unwanted contamination while the filters are being changed.



Back Harnesses for Increased Back Support and Higher Comfort



- When the system is ON, fitted with CleanAIR® filters

 2 When the system is ON, fitted with CleanAIR® filters
- incorporating pre-filter holder and spark arresters
- ³ When the system is OFF, fitted with decontamination plugs



Comfort Padded Harness R520044.1

Decontaminable Harness R510042



Decontamination Set for Chemical 2F/3F

Set of plugs for easy and thorough decontamination of respiratory units Chemical 2F/3F – ensuring ingress protection IP68.

Decontamination set 2F - 2× plug with external thread, 1× cap with internal thread R510046

Decontamination set 3F - 3× plug with external thread, 1× cap with internal thread



Decontamination Filter Cover

Protects the filter against water during decontamination process – ensuring ingress protection IP65.


Decontamination Filter Cover R580013



Chemically Resistant Hose Cover

Chemically resistant protective sleeve is made from Tychem-F that prevents the light hose from damage caused by splash of chemicals.

Hose Cover Chemical Resistant R700062C



Protective Unit Cover also Available

Washable protective cover available to protect the Chemical 2F unit from potentially corrosive agents and extend the units life.



Belt Options Available



Decontaminable belt made from rubber 'Hypalon' for easy decontamination.

Decontamination Belt R510051



Comfort padded belt with broad back part to efficiently spread weight of unit.

Comfort Padded Belt R710092

Two different hose options available

Option of a light flexible hose or a heavy-duty rubber hose with high chemical resistance for very demanding environments.





DIN Thread Filters to Suit Chemical 2F

The complete range of CleanAIR® canister filters offers a wide selection of filters for most industrial applications, pharmaceutical industry, laboratories and agriculture. The filters are supplied with a standard connection thread RD40×1/7" according to EN 148-1.

Particle filters catch a wide range of solid particles in the form of liquid and solid aerosols such as dust, smoke, fibres,

bacteria, viruses and radioactive particles.

Gas filters provide protection against contaminants in the form of gases and vapours.

Combined filters provide protection against a combination of contaminants in the form of gases, vapours and solid particles.

Particle Only Filters



P3 R500048.6

Combined Filters - Class 1



A1P3 R500357



A1B1E1P3 R500364

Combined Filters - Class 2



A2P3 R500157



A2B2P3 R500167



A2B2E2P3 R500164



A2B2E2K2P3 R500168



A2B2E2K2HgP3

Filter for organic gas and vapours with a boiling point lower than +65°C



A3AXP3 R500170

Filter Accessories

Pre-Filter traps the coarse particles and thus providing the life time of the main filter.

Pre-filter (pack of 10pcs) R500110 Odour Filter apart from trapping the coarse particles it even removes unpleasant odours. Spark Arrester prevents the main filter from being damaged hot sparks.

Spark Arrester R500112 Red Pre-Filter Keeper



CLICK HERE FOR PRODUCT SPEC

there's safe and there's Maxisafe.

